



BID SPECIFICATIONS

STANDARD

- * MATCHES 24H DISPLAY LINE AND COUNTERS
- * ALL TEMPERED, DOUBLE PANE GLASS ON FRONT AND SIDES
- * LED LIGHTING
- * TOP GLASS LIFTS UP (HYDRAULIC)
- * GALVANIZED STEEL CHASSIS CONSTRUCTION
- * INSULATED WITH DENSE NON-CFC ECOLOGIC POLYURETHANE FOAM
- * INSIDE STRUCTURE MADE OF HIGH GLOSS 304 STAINLESS STEEL
- * STAINLESS STEEL WORK SURFACE
- * DIGITAL DIAGNOSTIC CONTROL SYSTEM WITH PROGRAMMABLE DEFROSTING
- * REFRIGERATED DECK
- * REAR PLEXIGLASS SLIDING DOORS
- * SELF CONTAINED, AIR-COOLED CONDENSING UNIT
- * MULTIPLEXING CAPABILITY WITH GELATO, PASTRY, DELI, AND CHOCOLATE CASE APPLICATIONS
- * THE STANDARD LIMITED WARRANTY INCLUDES:
5 YEAR COMPRESSOR: 1 YEAR PARTS; 90 DAYS LABOR
- * FRONT AND SIDE PANELS OPTIONAL

OPTIONAL

- * CASTERS
- * GRANITE WORK SURFACE (OPERATOR SIDE)
- * REMOTE CONDENSING UNIT
- * FACTORY STANDARD MATTE WHITE FRONT AND SIDE PANELS



24h La Rossa Deli H20 8" Display Technical Specifications

Same as Pastry Cases, no drawer

Model no.	Case Heights	Case Lengths (Option #1)	Case Depth (Option #1)	Case Lengths (Option #2)	Case Depth (Option #2)	Crated Weights (lb)	Line Voltage	Amp Draws	Working Temp F
C83-FR H20/116/10	45.66"	39.36"	32.79"	40.86"	36.79"	650	220/1/60	12	38 - 41
C83-FR H20/116/15	45.66"	59.05"	32.79"	60.55"	36.79"	813	220/1/60	12	38 - 41
C83-FR H20/116/20	45.66"	78.73"	32.79"	80.23"	36.79"	988	220/1/60	14	38 - 41
** C83-24RVS 20.A45	37.79" - 45.66"	* A & B *	32.79"	* A & B *	36.79"	866	220/1/60	14	38 - 41

** 24H

OPTION #1

DIMENSIONS WITHOUT PANELS

46"H 8" DISPLAY

MATCHES LA ROSSA DISPLAY AND COUNTERS

24RVS 20.A45
A - CUSTOMER SIDE
A45 = 66.30"

24RVS 20.A45
46"H 8" DISPLAY

B - OPERATOR SIDE
A45 = 41.20"

OPTION #2

DIMENSIONS WITH FACTORY FINISHED PANELS


MATCHES LA ROSSA DISPLAY AND COUNTERS

24RVS 20.A45
A - CUSTOMER SIDE
A45 = 70.75"

B - OPERATOR SIDE
A45 = 42.58"

LA ROSSA & 24H PLAN VIEWS / SIDE VIEWS (SHOWN WITHOUT PANELS) / 3D VIEWS (FRONT & REAR)

LISTINGS:



ELECTRICAL CONNECTION:

Display cases are shipped with applicable junction box for hardwired installation
Options exist for several NEMA configurations
Plug and/or receptacle configurations are at the discretion of the electrical installer

NOTE:

Required ambient conditions: 75°F; 55% RH
Drawing and Specifications are subject to change without notice

CLABO USA INC.
2556 Barrington Court,
Hayward, CA 94545 USA
PH 800.672.2784
FAX 510.441.0401
<http://www.otl-america.com>