



BID SPECIFICATIONS

S
T
A
N
D
A
R
D

- * MATCHES 24H DISPLAY LINE AND COUNTERS
- * ALL TEMPERED, DOUBLE PANE GLASS ON FRONT AND SIDES
- * LED LIGHTING
- * TOP GLASS LIFTS UP (HYDRAULIC)
- * GALVANIZED STEEL CHASSIS CONSTRUCTION
- * INSIDE STRUCTURE MADE OF HIGH GLOSS 304 STAINLESS STEEL
- * REAR PLEXIGLASS SLIDING DOORS
- * STAINLESS STEEL WORK SURFACE

- * MULTIPLEXING CAPABILITY WITH GELATO, PASTRY, DELI, AND CHOCOLATE CASE APPLICATIONS
- * THE STANDARD LIMITED WARRANTY INCLUDES:
1 YEAR PARTS; 90 DAYS LABOR
- * FRONT AND SIDE PANELS OPTIONAL

O
P
T
I
O
N
A
L

- * CASTERS
- * GRANITE WORK SURFACE (OPERATOR SIDE)

- * FACTORY STANDARD MATTE WHITE FRONT AND SIDE PANELS



24h La Rossa Neutral H40 16" Display Technical Specifications

Model no.	Case Heights	Case Lengths (Option #1)	Case Depth (Option #1)	Case Lengths (Option #2)	Case Depth (Option #2)	Crated Weights (lb)	Line Voltage	Working Temp	Amp Draws	Shelf
N H40/116/10	45.66"	39.36"	32.79"	40.86"	36.79"	551	220/1/60	Ambient	4	1
N H40/116/15	45.66"	59.05"	32.79"	60.55"	36.79"	723	220/1/60	Ambient	5	1
N H40/116/20	45.66"	78.73"	32.79"	80.23"	36.79"	923	220/1/60	Ambient	6	1
N H40/116/A90	45.66"	42.32"	32.79"	47.07"	36.79"	715	220/1/60	Ambient	5	1
** C87-24N 20.A45	37.79" - 45.66"	* A & B *	32.79"	* A & B *	36.79"	710	220/1/60	Ambient	3	---
** C87-24N 40.A45	45.66" - 53.53"	* A & B *	32.79"	* A & B *	36.79"	780	220/1/60	Ambient	3	1

** 24H

OPTION #1

DIMENSIONS WITHOUT PANELS

OPTION #2

DIMENSIONS WITH FACTORY FINISHED PANELS

OPTION #1

DIMENSIONS WITHOUT PANELS

24N 40.A45
A - CUSTOMER SIDE
A45 = 66.30"

B - OPERATOR SIDE
A45 = 41.20"

OPTION #2


DIMENSIONS WITH FACTORY FINISHED PANELS

A - CUSTOMER SIDE
A45 = 70.75"

B - OPERATOR SIDE
A45 = 42.58"

LA ROSSA & 24H PLAN VIEWS / SIDE VIEWS (SHOWN WITHOUT PANELS) / 3D VIEWS (FRONT & REAR)

LISTINGS:



ELECTRICAL CONNECTION:

Display cases are shipped with applicable junction box for hardwired installation
Options exist for several NEMA configurations
Plug and/or receptacle configurations are at the discretion of the electrical installer

NOTE:

Required ambient conditions: 75°F; 55% RH
Drawing and Specifications are subject to change without notice

CLABO USA INC.
2556 Barrington Court,
Hayward, CA 94545 USA
PH 800.672.2784
FAX 510.441.0401
<http://www.otl-america.com>